

PURE 67 COMPACT (PU67V3)

JIDÉ
100% Made in Belgium

PU67V3-AC-SV-VE




PU67V3-NL-SV-VE



PU67V3-AC-SV-DM



PU67V3-NL-SV-DM



PU67V3-AC-SV-BN



PU67V3-NL-SV-BN



Configuration / Configuración




Ventilation / Ventilación

(SV) Without Ventilation /
Sin ventilación




Door / Puerta

(AC) Steel Door /
Puerta de acero



OR / O

(NL) New Look Door /
Puerta New Look




Interior / Interior

(VR) Vermiculite Interior /
Interior de vermiculita




OR / O

(BN) Black Concrete Interior /
Interior de hormigón negro



OR / O

(DM) Metal Decor Interior /
Interior decoración metálica



- Door closing system (2 positions)
Sistema de cierre de puerta (2 posiciones)

- Concrete hearth base
Solera de hormigón

- Air selector
Regulador de aire

- Secondary air diffuser
Difusor de aire secundario

- Adjustable feet
Patas regulables

- 1st vermiculite baffle, adjustable (3 positions)
1er deflector de vermiculita regulable en 3 posiciones

- 2nd fixed stainless steel baffle
2º deflector de acero inoxidable, fijo

- Door switch (ventilation stop)
Interruptor de puerta (paro de ventilación)


- If ventilated: with ventilation, airstat and speed
controller

Si es ventilado: con ventilación, airstat y regulador

Options / Opciones

Finishing frames / Marcos de acabado


Frame: 3 or 4 sides, width 40mm
Marco: 3 o 4 lados, ancho 40mm



OR / O

Drawn frame: thickness 10mm, depth 55mm or 20mm

Marco estirado: espesor 10mm, profundidad 55mm o 20mm



Reverse door mounting / Montaje de puerta invertido

Right hinge, left handle / Bisagra derecha, tirador izquierdo



Nozzle / Obturable

Shut-off hot air nozzle / Boquillas de convección obturables



Non shut-off nozzle at 45° (for the compact range) / Boquilla no obturable de 45° (para la gama Compact)







Vertical smoke outlet / Salida de humos vertical



Dimensions / Dimensiones

Fire viewing area / Vista del fuego



PURE 67
Compact

%- efficiency / Rendimiento %	power range / Potencia kW	Smoke outlet / Salida de humos	dimensions without frame / Dimensiones sin marco	Hot air / Aire caliente	double baffle / Doble deflector	CO-mg/Nm³
78	8-10	150	67 x 51 x 37	125	v	1125

COG mg/Nm³	NOX-mg/Nm³	flue gas temp / Temperatura de humos	seasonal efficiency / Rendimiento estacional	Particulate matter (mg/Nm³) / Partículas (mg/Nm³)	weight / Peso (kg)	logs / Troncos (cm)
91	38	293	67	15	83	1 x 50