

PURE L 67



Pure Manual - Ecological combustion - Sealed device

Steel door or New look - Without ventilation	Réf.	Ventil.	kW	
Pure L 67 manual - Steel door - verm. - 67x55x43	PUL67-55 M-A-SV	without	9,9	A
Pure L 67 manual - New look door - verm. - 67x55x43	PUL67-55 M-NL-SV	without	9,9	A

Real view of fire - L 516 mm - H 354 mm

Option

Interior vermiculite painted black

Reverse door fitting

Finishing frame in 1 piece	External dimensions
3-sided frame - 40 mm flat 3 mm	742 x 588
4-sided frame - 40 mm flat 3 mm	742 x 621
4-sided frame étiré 10 mm depth 20 mm	680 x 560
4-sided frame étiré 10 mm depth 55 mm	680 x 560

Included

Steel/New look door - manual combustion air regulation - external air intake Ø 100 mm - double baffles (vermiculite + inox) - stop embers - without ventilation - interior vermiculite - 45° angled stainless steel Ø 150 mm - nozzle for smoke outlet - colour antracite
2 warm air tubes Ø 125 mm - WITHOUT FINISHING FRAME: optional

PURE L 67



Pure Manual - Ecological combustion - Sealed device

Steel door or New look - With ventilation	Réf.	Ventil.	kW	
Pure L 67 manual - Steel door - verm. - 67x55x43	PUL67-55 M-A-AV	with	9,9	A
Pure L 67 manual - New look door - verm. - 67x55x43	PUL67-55 M-NL-AV	with	9,9	A

Real view of fire - L 516 mm - H 354 mm

Option

Speed controller with remote control

Speed controller with thermostat

Interior vermiculite painted black

2 small folated tubes of hot air Ø 125 mm

Air stop (in combination with hot air tube(s))

Reverse door fitting

Finishing frame in 1 piece	External dimensions
3-sided frame - 40 mm flat 3 mm	742 x 588
4-sided frame - 40 mm flat 3 mm	742 x 621
4-sided frame étiré 10 mm depth 20 mm	680 x 560
4-sided frame étiré 10 mm depth 55 mm	680 x 560

Included

Steel/New look door - manual combustion air regulation - external air intake Ø 100 mm - double baffles (vermiculite + inox) - stop embers - 2 centrifugal fans - interior vermiculite - 45° angled stainless steel Ø 150 mm - nozzle for smoke outlet - colour antracite - filters - WITHOUT FINISHING FRAME: optional

