

PURE XL16/9 MANUAL



PURE XL Manual - Ecological combustion - Sealed device

Steel door or New look - With ventilation	Réf.	Ventil.	kW	
Pure 16/9 manual - New look door - verm. - 100x60x47,5	PU16/9M.NL.AV	with	12,8	A
Pure 16/9 manual - Steel door - verm. - 100x60x47,5	PU16/9M.A.AV	with	12,8	A

Real view of fire - L 846 mm - H 404 mm

Option

Speed controller with remote control

Speed controller with thermostat

Interior vermiculite painted black

2 small folded tubes of hot air Ø 125 mm

Stop air (in combination with hot air tube(s))

Reserve door fitting

Finishing frames in 1 piece	External dimensions
3-sided frame - 40 mm flat 3 mm	1072 x 637,5
4-sided frame - 40 mm flat 3 mm	1072 x 671
4-sided frame étiré 10 mm depth 20 mm	1010 x 610
4-sided frame étiré 10 mm depth 55 mm	1010 x 610

Included

Steel/New look door - manual combustion air regulation - external air intake Ø 100 mm - double baffles (vermiculite + inox)
 stop embers - 2 centrifugal fans - interior vermiculite - 45° angled stainless steel Ø 200 mm - nozzle for smoke outlet
 colour antracite - filters - WITHOUT FINISHING FRAME: optional



PURE XL16/9



PURE Manual - Ecological combustion - Sealed device

Steel door or New look - Without ventilation	Réf.	Ventil.	kW	
Pure XL 16/9 manual - New look door - verm. - 100x60x47,5	PUXL16/9- M-NL-SV	without	12,8	A
Pure XL 16/9 manual - Steel door - verm. - 100x60x47,5	PUXL16/9- M-A-SV	without	12,8	A

Real view of fire - L 846 mm - H 404 mm

Option

Interior vermiculite painted black

Reserve door fitting

Finishing frames in 1 piece	External dimensions
3-sided frame - 40 mm flat 3 mm	1072 x 637,5
4-sided frame - 40 mm flat 3 mm	1072 x 671
4-sided frame étiré 10 mm depth 20 mm	1010 x 610
4-sided frame étiré 10 mm depth 55 mm	1010 x 610

Included

Steel/New look door - manual combustion air regulation - external air intake Ø 100 mm - double baffles (vermiculite + inox)
stop embers - without ventilation - interior vermiculite - 45° angled stainless steel P Ø 200 mm nozzle for smoke outlet - colour antracite
2 warm air tubes Ø 125 mm - WITHOUT FINISHING FRAME: optional



