

LODGE 70



Lodge - Ecological combustion - Sealed device

| LIFT door | Réf. | Ventil. | kW | |
|---|------|---------|----|---|
| Lodge 70 - New look door - verm. - 815x1549x490 | LO70 | without | 14 | A |

Real view of fire - L 559 mm- H 503 mm

Option

Kit ventilation with speedcontroller and airstat

Kit ventilation with speedcontroller and airstat

Speed controller with remote control

Speed controller with thermostat

Interior vermiculite painted black

| Finishing frame in 1 piece | External dimensions |
|---|---------------------|
| 4-sided frame - étiré 4 mm depth 55 mm | 665x676 |
| 4-sided frame - étiré 4 mm depth 100 mm | 677x688 |
| 4-sided frame - folded for panel - depth 55mm | 741x748 |
| 4-sided frame - étiré 10 mm depth 55 mm | 665x676 |
| 4-sided frame - étiré 10 mm depth 100 mm | 677x688 |

Included

New look door - manual combustion air regulation - external air intake Ø 125 mm - interior vermiculite - without ventilation
4 adjustable feet - lift door with side opening for cleaning the glass - double baffle - 2 modules for convection air connection
Ø 150 mm - stainless steel Ø 200 mm nozzle for smoke outlet - colour antracite - WITHOUT FINISHING FRAME: optional



