NORDIC PLUS 58/54





4-sided frame - 40 mm with folds 10 mm


Included


C€ A


| Nordic Plus - Forced convection - Ecological combustion - Sealed device | е | | | |
|---|-----------------|---------|------|---|
| | Réf. | Ventil. | kW | |
| Nordic Plus 58/54 - new look door - verm 58x54x42 | NO58/54.10 | with | 14,5 | А |
| Real view of fire - L 443 mm - H 280 mm | | | | |
| Option | | | | |
| Speed controller with remote control | | | | |
| Speed controller with thermostat (RT012) | | | | |
| Interior vermiculite painted black | | | | |
| Small tube of hot air Ø 125 mm | | | | |
| Stop air (only in combination with hot air tubes(s)) | | | | |
| Reverse door fitting | | | | |
| Finishing frame in 1 piece | External dimens | sions | | |
| 3-sided frame - 40 mm with folds 10 mm | 650x571,5 | | | |


New look door - automatic thermostat - external air intake \emptyset 100 mm - baffle vermiculite - double grill - ashtray - stop embers centrifugal fans - speed controller - airstat - interior vermiculite - 45° bent and straight stainless steel pipe for DS for smoke outlet (diameters see drawings) - filters - colour antracite - WITHOUT FINISHING FRAME: optional

650x610









| NOTES: |
|--------|
| |
| |
| |
| |
| |
| |
| |
| |
| |