

PURE L 67



PURE L Manual (without ventilation) - Ecological combustion (obligation to connect 2 hot air hoses) - Sealed device

Steel door (PUL67-55M-A-SV)

New look door (PUL67-55M-NL-SV)

PURE L Manual (with ventilation) - Forced convection - Sealed device

Steel door (PUL67-55M-A-AV)

New look door (PUL67-55M-NL-AV)

Kw	efficiency %	CO (mg/Nm ³)	COG (mg/Nm ³)	Dust (mg/Nm ³)	NOX (mg/Nm ³)	el_max (kw)	el_min (kw)	el_sb (kw)
10	78	1125	96	15	90	0,000	0,000	0,000

Options → External dimensions (mm) : 670 x 550 x 430

Flat frame PURE 67 - 3 sided - 40mm → 742 x 588

Flat frame PURE 67 - 4 sided - 40mm → 742 x 621

Frame PURE 67 - drawn steel - 4 sided - 10 mm - depth 20mm → 680 x 560

Frame PURE 67 - drawn steel - 4 sided - 10 mm - depth 55mm → 680 x 560

Speed controller with airstat (with ventilation)

Speed controller with thermostat ambient temperature (with ventilation)

Hot air tubes kit 125 Ø+ Air stop kit

Supplement hot air tubes kit 125 Ø+ Air stop kit (with ventilation)

Reserve door fitting

Black painted vermic. interior

Included

Manual combustion air regulation - external air intake Ø 100 mm - double baffles (vermiculite + inox) - stop embers - without ventilation - interior vermiculite - 45° angled stainless steel Ø 150 mm - nozzle for smoke outlet - colour antracite 2 warm air tubes Ø 125 mm - WITHOUT FINISHING FRAME (following your choice)

Real view of fire (mm) - 516 x 354

